

TABOND 3043 ADHESIVE RESIN

TABOND 3043 is HDPE modified with maleic anhydride functional groups which promote bonding with different materials like polar polymers, metals and surface treated glass.

Characteristics:

- Strong adhesion to aminosilane treated glass, Nylon, EVOH, PET, PBT, PC, aluminium, copper, brass and steel.
- Adhesion durability
- Polyolefin like properties and processing

Applications:

- Tube co-extrusion - PE with PA or EVOH
- Blow moulding co-extrusion - PE with PA or EVOH
- Sheet co-extrusion - PE with PA, EVOH, PET, PBT, PP
- Bonding agent for extrusion coating of aluminium or steel with PE (also for steel coated with epoxy resin)
- Chemical coupling agent for PE composites
- and Wire&Cable compounds containing fillers such as ATH, $MG(OH)_2$, glassfiber etc. (recommended concentration 1.5 - 5%)
- Compatibilizer for alloys of PE with PA, EVOH, PET, PP or PBT (recommended concentration 2-5%).
- Additive for recycling of polyolefin's with polar polymers.

Physical properties

Density	0.958	g/cm^3
Melt flow index (2.16 kg, 190 °C)	2,6	[g/10 min] min
Melting point (DSC)	132,2	°C

Appearance: White, free -flowing pellets.

Storage and handling: TABOND 3043 contains traces of non-bonded maleic anhydride, which is an irritating substance. The work place should have an effective ventilation system. Please pay attention to the instruction in the safety data sheet.

Packaging: TA-BOND 3043 is supplied in 25 kg bags.